

フレキシブルLEDモジュール
FX50-LED-WP (R,G,B) 入力特性表

LEDモジュール入力電力値合計を使用直流水源装置の最大使用W数以下でお使いください

形式 (□口・色記号) (R,G,B)	全長 (mm)	LED モジュール 入力電力 (W)	LEDモジュール入力電力一覧											
			直流水源装置			ELD2475F 非調光			ELD24150FDD DALI調光(5%~100%)			ELD2-24240FD PWM調光(3%~100%)		
			LEDモジュール 入力電力 最大使用W数			59W 直列配線LEDモジュール長合計長さ 500mm以下			105W(90W)* 直列配線LEDモジュール長合計長さ 500mm以下			168W(144W)* 直列配線LEDモジュール長合計長さ 500mm以下		
FX50-LED 50 □□-WP	90	0.37	0.03	2.5	0.045	2.3	0.05	3.9	0.06	4.1	0.07	3.5	0.10	5.6
FX50-LED 100 □□-WP	140	0.72	0.04	2.9	0.05	2.8	0.06	4.3	0.06	4.5	0.08	4.0	0.10	6.0
FX50-LED 150 □□-WP	190	1.1	0.04	3.4	0.05	3.2	0.06	4.8	0.07	4.9	0.08	4.5	0.11	6.5
FX50-LED 200 □□-WP	240	1.4	0.05	3.8	0.05	3.6	0.07	5.1	0.07	5.3	0.09	4.8	0.11	6.9
FX50-LED 250 □□-WP	290	1.8	0.05	4.3	0.05	4.1	0.07	5.6	0.07	5.8	0.09	5.3	0.11	7.4
FX50-LED 300 □□-WP	340	2.1	0.05	4.7	0.05	4.5	0.08	6.0	0.07	6.2	0.10	5.7	0.11	7.7
FX50-LED 400 □□-WP	440	2.8	0.06	5.5	0.06	5.3	0.08	6.9	0.08	7.0	0.10	6.6	0.12	8.6
FX50-LED 450 □□-WP	490	3.2	0.07	6.1	0.06	5.8	0.09	7.4	0.08	7.5	0.11	7.1	0.12	9.1
FX50-LED 500 □□-WP	540	3.5	0.07	6.4	0.06	6.2	0.09	7.7	0.08	7.9	0.11	7.5	0.12	9.4
FX50-LED 550 □□-WP	590	3.9	0.08	6.9	0.06	6.7	0.10	8.2	0.08	8.3	0.12	8.0	0.12	9.9
FX50-LED 600 □□-WP	640	4.2	0.08	7.3	0.06	7.1	0.10	8.6	0.08	8.7	0.12	8.4	0.12	10.3
FX50-LED 650 □□-WP	690	4.6	0.08	7.8	0.06	7.6	0.11	9.1	0.09	9.2	0.13	8.9	0.13	10.8
FX50-LED 700 □□-WP	740	4.9	0.09	8.2	0.06	7.9	0.11	9.5	0.09	9.6	0.13	9.3	0.13	11.2
FX50-LED 750 □□-WP	790	5.3	0.09	8.7	0.07	8.4	0.11	10.0	0.09	10.0	0.14	9.8	0.13	11.7
FX50-LED 800 □□-WP	840	5.6	0.10	9.1	0.07	8.8	0.12	10.5	0.09	10.5	0.14	10.1	0.13	12.0
FX50-LED 850 □□-WP	890	6.0	0.10	9.6	0.07	9.3	0.12	11.0	0.09	11.0	0.14	10.7	0.13	12.5
FX50-LED 900 □□-WP	940	6.3	0.10	10.0	0.07	9.7	0.13	11.0	0.10	11.5	0.15	11.0	0.14	12.9
FX50-LED 950 □□-WP	990	6.7	0.11	10.5	0.07	10.0	0.13	11.5	0.10	12.0	0.15	11.5	0.14	13.4
FX50-LED 1000 □□-WP	1040	7.0	0.11	11.0	0.07	10.5	0.14	12.0	0.10	12.0	0.16	11.9	0.14	13.7
FX50-LED 1050 □□-WP	1090	7.4	0.12	11.5	0.08	11.0	0.14	12.5	0.10	12.5	0.16	12.4	0.14	14.2
FX50-LED 1100 □□-WP	1140	7.7	0.12	12.0	0.08	11.5	0.14	13.0	0.11	13.0	0.17	12.8	0.14	14.6
FX50-LED 1150 □□-WP	1190	8.1	0.13	12.5	0.08	12.0	0.15	13.5	0.11	13.5	0.17	13.3	0.15	15.1
FX50-LED 1200 □□-WP	1240	8.4	0.13	12.5	0.08	12.5	0.15	14.0	0.11	14.0	0.17	13.7	0.15	15.5
FX50-LED 1250 □□-WP	1290	8.8	0.13	13.0	0.08	13.0	0.16	14.5	0.11	14.5	0.18	14.2	0.15	16.0
FX50-LED 1300 □□-WP	1340	9.1	0.14	13.5	0.08	13.0	0.16	14.5	0.11	14.5	0.18	14.6	0.15	16.3
FX50-LED 1350 □□-WP	1390	9.5	0.14	14.0	0.08	13.5	0.17	15.0	0.12	15.0	0.19	15.1	0.16	16.8
FX50-LED 1400 □□-WP	1440	9.8	0.15	14.5	0.09	14.0	0.17	15.5	0.12	15.5	0.19	15.5	0.16	17.2
FX50-LED 1450 □□-WP	1490	10.2	0.15	15.0	0.09	14.0	0.17	16.0	0.12	16.0	0.20	16.0	0.16	17.7
FX50-LED 1500 □□-WP	1540	10.5	0.16	15.5	0.09	14.5	0.18	16.5	0.12	16.5	0.20	16.3	0.16	18.0
FX50-LED 1550 □□-WP	1590	10.8	0.16	15.5	0.09	15.0	0.18	17.0	0.12	16.5	0.20	16.7	0.15	17.5
FX50-LED 1600 □□-WP	1640	11.2	0.16	16.0	0.10	15.5	0.19	17.5	0.13	17.0	0.21	17.2	0.16	18.9
FX50-LED 1650 □□-WP	1690	11.5	0.17	16.5	0.10	15.5	0.19	17.5	0.13	17.5	0.21	17.6	0.17	19.3
FX50-LED 1700 □□-WP	1740	11.8	0.17	17.0	0.10	16.0	0.19	18.0	0.13	18.0	0.22	18.0	0.17	19.6
FX50-LED 1750 □□-WP	1790	12.1	0.18	17.5	0.10	16.5	0.20	18.5	0.13	18.5	0.22	18.4	0.17	20.0
FX50-LED 1800 □□-WP	1840	12.4	0.18	17.5	0.10	17.0	0.20	18.5	0.13	18.5	0.22	18.7	0.17	20.4
FX50-LED 1850 □□-WP	1890	12.7	0.18	18.0	0.10	17.0	0.20	19.0	0.14	19.0	0.23	19.1	0.17	20.8
FX50-LED 1900 □□-WP	1940	13.1	0.19	18.5	0.11	17.5	0.21	19.5	0.14	19.5	0.23	19.6	0.18	21.2
FX50-LED 1950 □□-WP	1990	13.4	0.19	19.0	0.11	18.0	0.21	20.0	0.14	20.0	0.24	20.0	0.18	21.6
FX50-LED 2000 □□-WP	2040	13.7	0.20	19.5	0.11	18.5	0.22	20.5	0.14	20.5	0.24	20.4	0.18	22.0
FX50-LED 2050 □□-WP	2090	14.0	0.20	19.5	0.11	18.5	0.22	20.5	0.14	20.5	0.24	20.8	0.18	22.3
FX50-LED 2100 □□-WP	2140	14.4	0.20	20.0	0.11	19.0	0.22	21.0	0.15	21.0	0.25	21.3	0.18	22.8
FX50-LED 2150 □□-WP	2190	14.7	0.21	20.5	0.12	19.5	0.23	21.5	0.15	21.5	0.25	21.6	0.19	23.2
FX50-LED 2200 □□-WP	2240	15.0	0.21	21.0	0.12	20.0	0.23	22.0	0.15	22.0	0.26	22.0	0.19	23.6
FX50-LED 2250 □□-WP	2290	15.4	0.22	21.5	0.12									